



BOLLETTINO TECNICO



SISTEMI INNOVATIVI

REV. 291016

KETTY PAINTS

Superior quality washable water-based paint for interiors

CHARACTERISTICS

KETTY PAINT is a water-based paint with high covering power, breathable, washable, superior quality, with a smooth matt aesthetic effect, eco-friendly, white or coloured, suitable for interiors.

FIELDS OF USE

KETTY PAINT, given its special formulation, is suitable for quality interior interventions and is ideal for painting bathrooms and kitchens.

PREPARATION OF THE SUPPORT

The substrate must be completely dry, clean, free from dust, oil, grease or other types of dirt, flaking parts or layers of separating substances. In the case of previous poorly adhering paints, remove them completely using suitable scrapers and brushes. Before applying **KETTY PAINT**,

especially on absorbent mineral substrates such as our **STUCCO COC, STUCCO COC 747**, etc., apply a coat of **PRESTO**, a water-based fixative, appropriately diluted with clean water in a ratio of 1:3 to 1:7.

HOW TO USE

After diluting the product with clean water by 20 to 40% maximum, mix it carefully and apply it in two coats, spaced approximately 8-10 hours apart, with a brush or roller, crossing the brush strokes, or even by spraying.

WARNINGS

- Mix the product thoroughly, adding water slowly until the appropriate viscosity is obtained.
- The first coat can be more diluted than the second to facilitate its penetration into the substrate.
- Do not apply below 7°C and above 30°C, in strong winds or blazing sun.
- Brushes and tools should be washed immediately afterwards the use.
- Store the product away from frost.
 - The white product can be colored using suitable quality universal colorants.
- Apply **KETTY PAINT** once the primer-fixative has completely dried.

BOLLETTINO TECNICO



REV. 291016

SPECIFICATION ITEM

Application of water-based paint with high covering power, breathable, washable, superior quality, with a smooth matt aesthetic effect, eco-friendly, white or coloured, suitable for interiors, indicated for quality interventions inside and ideal for painting bathrooms and kitchens, to be diluted with clean water from 20 to 40% maximum, to be applied in two coats with a brush, roller or spray, after applying a coat of **PRESTO BUFFA** fixative appropriately diluted, with a coverage of 0.20 / 0.25 lt per m² for two coats, such as **KETTY PAINT BUFFA**.

TECHNICAL DATA

DILUTION	with clean water from 20 to 40% maximum vinyl-
COMPOSITION	versatic copolymers in aqueous dispersion 1.7 ± 0.05 kg / lt
SPECIFIC WEIGHT	30000 ± 5000 cps at
VISCOSITY	20° C smooth-matt white or
FILM APPEARANCE	coloured. It is
COLOR	also compatible with common quality universal dyes. - dry to the touch two hours - dry in depth 24 hours 0.20 /
DRYING	0.25 lt per m ² for two coats 4 / 14 lt buckets
TRIP	
PACKAGES	
STORAGE	18 months if stored in intact packaging, away from heat, frost and humidity. Non-toxic product.
TOXICITY	

ATTENTION

The information, instructions and indications above are the result of our best technical and applicative knowledge; nevertheless, they are to be considered purely indicative. Therefore, it is the user's responsibility to verify, assuming full responsibility, the compatibility of the products with the intended use, since we cannot intervene directly on the conditions of the construction sites and the methods of carrying out the works. In this regard, a preliminary test is recommended in order to verify the suitability of the product for the intended use.