



## SISTEMI INNOVATIVI

REV. 125016

### MAX ETHYL

Protective consolidant with strong penetration

#### CHARACTERISTICS

MAX ETIL is a ready-to-use, white, highly breathable, highly penetrating protective consolidant based on modified silicates, ideal for the treatment of crumbling surfaces.

#### FIELDS OF USE

MAX ETIL is indicated for the consolidating treatment of crumbling surfaces such as plasters, mineral coatings, etc., as part of specific restoration cycles, both internally and externally.

#### PREPARATION OF THE SUPPORT

Before applying MAX ETIL, make sure that the substrate is dry, clean and free from dust, oils and greases, paints, flaking parts and layers of separating substances.

#### HOW TO USE IT

Apply MAX ETIL with a brush, roller or spray in one or more coats depending on the substrate, taking care to spread the product evenly, in order to avoid dripping. Allow at least 6-8 hours between one coat and the next.

#### WARNINGS

- Since the product is ready to use, apply this and which, without the addition of foreign materials.
- Do not apply when there is a threat of rain or rain.
- Do not apply when there is strong sun and strong wind.
- MAX ETIL must be applied at temperatures between 5° C ~ 30° C.
- Do not apply excessive amounts of the product to avoid dripping.

# BOLLETTINO TECNICO



REV. 125016

## SPECIFICATION ITEM

Protective consolidant with strong penetration, ready to use, white in colour, highly breathable, based on modified silicates, suitable for the consolidating treatment of crumbling surfaces such as plasters, mineral coatings, etc., as part of specific restoration cycles, both indoors and outdoors, to be applied in one or more coats with a brush, roller or spray, with a consumption of 0.15 / 0.25 lt per m<sup>2</sup> per coat, type **MAX ETIL FUNNY**.

## TECHNICAL DATA

<b>DILUTION</b>	ready to use
<b>COMPOSITION</b>	modified silicate solution
<b>DRYING</b>	about 6-8 hours
<b>TRIP</b>	0.15 / 0.25 lt per m <sup>2</sup> per coat white
<b>COLOR</b>	
<b>PACKAGES</b>	1x12 lt or 5x4 lt boxes, 25 lt cans
<b>STORAGE</b>	12 months, in intact packaging away from sources of frost, heat and humidity
<b>TOXICITY</b>	ventilate the areas where it is applied. Use gloves and protective glasses. If the product comes into contact with the skin, wash with soap and water and rinse thoroughly.

## ATTENTION

The information, instructions and indications above are the result of our best technical and applicative knowledge; nevertheless, they are to be considered purely indicative. Therefore, it is the user's responsibility to verify, assuming full responsibility, the compatibility of the products with the intended use, since we cannot intervene directly on the conditions of the construction sites and the methods of carrying out the works. In this regard, a preliminary test is recommended in order to verify the suitability of the product for the intended use.