



# marmox multiboard

Marmox Multiboard is a lightweight, high-performance tile backer board, used for waterproofing, dry-lining and thermal insulation, offering the best long-term adhesion in its class. Marmox Multiboard consists of a core of extruded polystyrene bonded between layers of fibreglass reinforced polymer concrete.

Thicknesses range from 4mm to 80mm allowing Marmox Multiboard to be used to provide a platform for tiling, a waterproof barrier, thermal insulation on walls, floors and ceilings. Multiboard is easy to cut and shape providing freedom of design and quick installation.

REF	THICKNESS (MM)	WIDTH (MM)	LENGTH (MM)	U VALUE (W/m <sup>2</sup> K)	R VALUE (m <sup>2</sup> .K/ W)	QUANTITY PER PALLET
4 MB 125	4	600 900 1200	1250	9.9	0.06	165
6 MB 125	6			7	0.12	150
10 MB 250	10		2500	3.5	0.25	215
125 MB 250	12.5			2.7	0.33	150
20 MB 250	20			1.5	0.56	106
30 MB 250	30			1	0.86	75
40 MB 250	40			0.7	1.16	60
50 MB 250	50			0.57	1.47	45
80 MB 250	80			0.5	2.33	25

Panels are available in 260cm length on special order