



INTERNATIONAL SYSTEMS

REV. 191015

LIBECCIO FINISH

Premixed superfine mineral plaster based on highly breathable marble dust for interiors

CHARACTERISTICS

LIBECCIO FINISH is a premium, white, superfine, highly breathable mineral plaster, with a smooth, superior-quality finish. It is based on marble powder, hydraulic binders, and specific additives, and is suitable for interiors.

It is used on new surfaces, including walls and ceilings, before painting. It is also extremely easy to apply. If desired, it can be painted or left in its natural state for a smooth marble effect.

FIELDS OF USE

The LIBECCIO FINISH is used indoors as a high-quality undercoat/smooth finish on new, smooth or rough surfaces, on walls and ceilings, before painting with water-based paints or products from the Contrasti line. It is ideal for our TONACHINO LIBECCIO, TONACHINO LIBECCIO EXTRA, TONACHINO LIBECCIO PLUS, RASOX PLUS F, etc.

PREPARATION OF THE SUPPORT

Make sure the surface is clean and free of dust, oil, grease, paint, flaking particles, and layers of separating substances. Any imperfections must be removed and smoothed before applying the LIBECCIO FINISH. Moisten the surface before application only if necessary.

APPLICATION METHOD: To mix with a low-speed electric stirrer, add approximately 9.5 liters of clean water to each 25 kg bag. Mixing time should not exceed 5 minutes.

Let the product rest for approximately 10 minutes before using. Then, using a stainless steel trowel, apply two coats: smooth the first coat and, after approximately 30-60 minutes, apply the second coat, smoothing until achieving a smooth and even surface. As soon as the **LIBECCIO FINISH** is dry, after applying the appropriate primers, proceed with painting the surfaces if desired. **WARNINGS**

- The LIBECCIO FINISH must be used as is, without the addition of any foreign materials.
- The processing time varies depending on the temperature and, in any case, the LIBECCIO FINISH must be applied within 2 hours of mixing.
- We recommend using specialized personnel.
- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply at relative humidity below 35% or above 85%.
- Avoid application in strong winds and strong sunlight.

TECHNICAL DATA SHEET



REV. 191015

SPECIFICATION ITEM

For interior surfaces, use a premixed, white, superfine, highly breathable, high-quality, smooth-finish mineral plaster, made with marble dust, hydraulic binders, and specific additives. Suitable for new substrates, both smooth and rough, on walls and ceilings, it is ideal for TONACHINO LIBECCIO BUFFA, TONACHINO LIBECCIO EXTRA BUFFA, TONACHINO LIBECCIO PLUS BUFFA, RASOX PLUS F BUFFA, etc., to be applied in two coats with a smooth stainless steel trowel, with an average consumption of 1.2-1.6 kg per m² for two coats, such as FINITURA LIBECCIO BUFFA.

TECHNICAL DATA

DILUTION	Approximately 38%
APPEARANCE	
COMPOSITION	powder - marble powder - hydraulic binders - specific additives
DRYING	
SANDING INTERVAL	Approximately 6-8 hours at 23°C
OVERPAINTABILITY	Minimum 24 hours
COVERAGE	24-48 hours
COLOR	1.2-1.6 kg per m ² for two coats
PACKAGING	White 25 kg bags
STORAGE	12 months if stored in unopened packaging, away from heat, frost, and humidity
TOXICITY	See safety data sheet

These times, calculated at 22°C, are lengthened by low temperatures and reduced by heat.

ATTENTION

The information, specifications, and guidelines above are based on our best technical and application knowledge; however, they are intended to be purely indicative. Therefore, it is the user's responsibility to verify, at his or her sole discretion, the compatibility of the products with the intended use, as we cannot directly influence site conditions or the methods of execution. Therefore, a preliminary test is recommended to verify the product's suitability for the intended use.



Buffa Malta
Wills St, Paola PLA2233
Tel. 9929 3172

buffa@t4bservices.com
www.buffamalta.com

I valori di questo bollettino tecnico si riferiscono a prove di laboratorio effettuate in ambiente condizionato. Essi possono variare nella messa in opera a causa delle condizioni atmosferiche.

PROFESSIONISTI IN EDILIZIA